CAT. N° 4 122 25



SPD - T2 - IMAX 20 KA/POLE - 3P+N - NEUTRAL ON LEFT HAND SIDE

Pack (number of units)	1
Volume (dm³)	0,701
Weight (g)	351,00

Product characteristics

T2 SPDs

- SPDs with plug-in modules and status indicators:
  - Green: SPD operational
  - Orange: plug-in modules to be replaced

T2 - Imax 20 kA/pole

- SPDs recommended for small installations
- Up: 1.2 kV - In: 5 kA/pole - Uc: 320 V~
- Earthing systems : TT, TNC, TNS
- Recommended MCB: DX³ 20 A - C curve
- 1P+N and 3P+N: L-N and N-PE protection modes (common and differential modes), the N pole being protected by encapsulated spark gaps. Also called 1+1 and 3+1
- Number of poles : 3P+N
- Neutral position : Left
- Remote status monitoring (FS contact) : No
- Number of modules : 4

General characteristics

Class II (T2) low voltage SPDs

- Protection against transient overvoltagess for 230/400 V~ power networks (50/60 Hz). SPDs compliant with EN/IEC 61643-11 standards
- Recommended for distribution boards

Documentation

Catalogue pages & additional information

- Technical page (p.074-075)
- Description page (p.077)
- Technical page (p.079)
- Technical page (p.080-081)
- Dimensions of din-rail equipment

Installation & technical data

- F02060EN_05

Installation instructions & related documents

- LE07561AA_6

Agreements & certificates of conformity

- OC / CB - AT 4283

* All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis : before-tax price list, May 2018

The information given in this e-catalogue (characteristics and dimensions) may be amended, and therefore does not represent an undertaking on our part. The e-catalogue is reserved for professionals only. You are also reminded that all products must be installed by a qualified professional in accordance with the installation rules.